# Who Said Monitoring Is Boring?

#### Pradeep Buddharaju

Computational Physiology Lab 366 Philip G. Hoffman Hall University of Houston Houston, TX 77204 USA pbuddharaju@uh.edu

### Dvijesh Shastri

Computational Physiology Lab 366 Philip G. Hoffman Hall University of Houston Houston, TX 77204 USA dshastri@uh.edu

#### Anitha Mandapati

Computational Physiology Lab 220 Philip G. Hoffman Hall University of Houston Houston, TX 77204 USA amandapati@uh.edu

Copyright is held by the author/owner(s). CHI 2011, May 7–12, 2011, Vancouver, BC, Canada. ACM 978-1-4503-0268-5/11/05.

#### Swati Vaidya

Computational Physiology Lab 220 Philip G. Hoffman Hall University of Houston Houston, TX 77204 USA svaidya@mail.uh.edu

## Ioannis Pavlidis

Computational Physiology Lab 218 Philip G. Hoffman Hall University of Houston Houston, TX 77204 USA ipavlidis@uh.edu

### Abstract

In this article, we extend our previous work [1], which blended gaming in monotonous security tasks to increase operator engagement and enjoyment. Specifically, we expand from a single game presented in [1] to an assortment of games that appeal to different tastes. These include a shooting game, a racket game, and two puzzle games. All games are designed in a way that attracts instead of detracting attention to the monitoring screens. In addition to the game set, we also include a web browser capability symbiotic to the monitoring task. All these applications are tested in a quite realistic pilot experiment, where subjects are monitoring live security feeds. This is in contrast to the experiment on a pre-recorded video feed reported in [1]. The results demonstrate that subject engagement and enjoyment is significantly higher when the monitoring task is multiplexed with imaginative interactive options. This improvement in job satisfaction is achieved without sacrificing performance, as measured by detection of suspicious activities.

### Keywords

Human-Computer Interaction, security monitoring, human engagement and performance, computer games

# ACM Classification Keywords

H5.2. Information interfaces and presentation: User Interfaces – Evaluation/methodology, Input devices and strategies, Prototyping, Interaction styles.

## **General Terms**

Experimentation, Human Factors, Performance

## Introduction

Alas, some of the most critical activities in our society are among the most boring ones. Security monitoring is a quintessential example, where guards have to scan through rarely interesting security feeds for hours on end. The aim is noble – to protect valuable assets and human lives. The process, however, is downright boring and has a corrosive effect on job satisfaction, something that ultimately may compromise performance.

Monotonous tasks, such as security monitoring, can benefit from some excitement that an entertainment option could offer. The question is how exactly. Many studies show that some forms of entertainment (e.g., games) can improve human performance at work [4] or education [2]. For instance, Chao et al. introduced a game application for computer administration tasks [3]. Several computer games have proved effective enhancers of human behavior. For example, Dance-Dance Revolution [5], and EyeToy [6] were found to increase physical activity. Game design by Khaled et al. emerged as a persuasive alternative for smoking cessation [7].

Introducing a form of entertainment in a monotonous task implies some sort of interruption. Studies show that interruptions, when appropriate, do not negatively affect performance at work. In fact, they reduce boredom in many cases [8]. Hence, an innovative form of interruption may render monitoring more enjoyable.

Based on this principle, we have recently introduced a mildly interactive computer game in security monitoring [1]. The operator was using an iPhone as a wand to catch apples that occasionally were falling on the video security feeds. The game design encouraged attention on the security video feeds while offering some entertainment. This was a symbiotic design where the `break' option managed to attract instead of detracting attention from the job. This certainly casts the concept of `interruption' in a whole new light.

In the present article, we take this to the next level by introducing an assortment of gaming options that ascribe to the same symbiotic spirit, but cater different tastes. These include a shooting game, a racket game, and two puzzle games. Most importantly, we extend the space of symbiotic design beyond games, by including a mini-browser option. Web browsing is a ubiquitous activity and we experiment with an initial design to see if it can be multiplexed with the monitoring task.

The results of a controlled pilot experiment on live security feeds, demonstrate the significant entertainment value of all these options. This is achieved without any negative effects on the operators' performance. Our latest work opens the way for largescale field studies and points to an ever-expanding set of symbiotic interactive options.

# **Experimental Design**

We used the security video fees from three cameras in corresponding computer labs at the University of Houston. Use of these feeds for the purposes of this research was authorized by the local Institutional Review Board (IRB) and university administration.

A total of 4 participants (3 males and 1 female) volunteered for this study. The experiment featured two trials of hour-long monitoring for each participant. The 'without symbiotic activity' trial represented the standard monitoring task. The 'with symbiotic activity' trial represented the monitoring task laced with the specially designed interactive options. The order of trials was randomized to ensure unbiased results.



Slider puzzle where puzzle pieces are formed using live video footage



**figure 1.** Experimental setup – Participant monitoring live security video footage while solving a slider puzzle

During the experimental trials, we staged random unlawful activities in these lab rooms, such as stealing (e.g., stealing books, laptops, and some documents) as well as property damage (e.g., destroying posters).

Figure 1 illustrates the experimental setup. Before the experiment began, the participants were asked to complete a biographic questionnaire. After completing the questionnaire, they were asked to relax for 3 minutes. We let the participants listen to soft/calm music during the relaxation phase. This helped to isolate effects of other stress factors that the participants may have carried from earlier in the day.

Then the participants were asked begin the trail by monitoring the live security feeds from three lab rooms, and to record any suspicious activities they notice. Based on their responses, we derived measures of performance.

The participants were also required to fill out feedback forms at the end of each trial. Their responses in these forms, along with the application usage record, were used to quantify the engagement and entrainment value of the `without symbiotic activity' versus `with' symbiotic activity trials.

Below we describe the interactive symbiotic applications that were available to participants during the `*with symbiotic activity* trials.

### Wand Games

The design of these games is similar to the 'Apple Catching Game' presented in [1]. They are based on a client-server architecture, whereby the game runs on the server (Mac) and is controlled via an iPhone (the client). The two new games in this category are: a 'Shooting Game', where the player aims to shoot

enemy objects and a '*Racket Game*', where the player aims to send a ball back to the screen. In both cases, the player uses an iPhone as the wand.



**figure 2.** Mini web browser tool presented in an open space between the security video feeds

### Puzzle Games

We have developed a '*Slider Puzzle*', where the live surveillance video is split into random tile-shaped pieces, and a '*Jigsaw Puzzle*' where the video is split into random jigsaw-shaped pieces. The goal for the player is to rearrange the puzzle pieces, so that s/he recreates a copy of the live security feed that runs on the side. Figure 1 shows an example of the '*Slider Puzzle*' game. Since the puzzle pieces are formed using live video footage, the player inherently pays attention to the monitoring screen.

#### Mini Web Browser

We provide a mini web browser option for participants, who would like to go through news reading or other online viewing during the monitoring task. The browser is presented between the security video feeds (as shown in Figure 2) to ensure that the participant still pays some attention to the feeds via peripheral vision.

# **Experimental Results and Discussion**

We used subjective feedback survey data to evaluate the participants' enjoyment and performance while performing the task. Table 1 summarizes the test results for the performance variables. It shows that only *false negative* has favorable response with the activity tools, but the difference was not statistically significant with 95% confidence interval. Thus, the participants' performance remained on par in both trials. The symbiotic tools did not degrade performance at all.

Variable	Mean Diff	T- ratio	P- value	Better with tools?	Statistically Significant?	
Correct Identific ation	0.25	0.39	0.35	NO	NO	
False positive	0.75	0.1	0.1	NO	NO	
False negative	-0.25	- 0.39	0.35	YES	NO	

**Table 1.** Paired T-test results for the performance variables

Table 2 summarizes the test results for the subjective variables. It shows that all subjective variables except for *self-reported performance* and *effort* have positive response with the interactive activity tools. One important observation is that the differences were statistically significant in *motivation*, *entertainment*, and *mental demand* with 95% confidence interval

(highlighted in yellow color in Table 2). This result shows that the symbiotic tools made the monitoring job more entertaining and mentally engaging and boosted the participants' motivation.

Variable	Mean Diff	T- ratio	P- value	Better with tools?	Statistic ally Significa nt?	
Motivation	-3.5	-2.94	0.03	YES	YES	
Entertain ment	-5.25	-6.14	0.004	YES	YES	
Mental Demand	-2.5	-2.4	0.004	YES	YES	
Performan ce	0.25	0.19	0.43	NO	NO	
Effort	1.25	1.46	0.11	NO	NO	
Physical Demand	-1.25	-1.21	0.15	YES	NO	

**Table 2.** Paired T-test results for the subjective variables

Table 3 summarizes the results for each of the symbiotic activity tools based on participant feedback. For each variable (e.g., *Entertainment*), feedback from all the participants is collected and the arithmetic mean is reported. All variables were scored in the range of zero to nine integer values where zero means the lowest level (e.g., no entertainment), and nine means the highest level (e.g., most entertaining). It can be inferred from the results that the participants found all tools entertaining. An interesting observation is that the participants found the puzzle games to be hardest

(higher *difficulty level* values), and hence more mentally demanding (higher *mental demand* values). However, the differences for these variables are not statistically significant with 90% confidence interval. The only variable with statistically significant difference is *time spent for each game* (highlighted in yellow color in Table 3), showing that the participants spent most time on the shooting game and the web-browsing tool -clearly the most popular options in this symbiotic set.

## Conclusions

We developed an assortment of symbiotic activity tools that helps to improve users' engagement and entertainment in a monotonous monitoring task. We used as test bed monitoring of live security video footage – a flat out boring task. The tool set comprised two wand-based games and two puzzle games overlaid on top of the security video feeds, as well as a mini web-browsing tool presented between the video feeds. The experimental results confirm our hypothesis that integrating symbiotic activity tools transforms a boring monitoring task by improving operator enjoyment and engagement without sacrificing performance. Heartened by the positive results, we plan to scale-up the experiment, conducting a large-scale field study with an ever-expanding set of symbiotic applications.

# Acknowledgements

This material is based upon work supported by NSF award # IIS-1049004 entitled: 'Improving Human Engagement and Enjoyment in Routine Activities'. Any opinions, findings, and conclusions or recommendations are those of the authors and do not necessarily reflect the views of the funding agency.

Variable	Shooting	Racket	Slider puzzle	Jigsaw puzzle	Web Browsing	P- value	Statistically Significant?
Entertainment level	6.00	6.00	7.50	7.00	5.33	0.13	NO
Activity liking	5.00	3.00	3.75	1.75	5.00	0.12	NO
Difficulty level	3.33	2.50	5.00	6.00	5.33	0.26	NO
Mental demand	3.33	4.00	7.00	9.00	5.33	0.36	NO
Distraction level	5.00	5.00	4.50	4.00	5.66	0.17	NO
Difficulty in balancing monitoring and symbiotic activities	3.33	3.50	4.00	5.00	5.33	0.17	NO
Time spent on each game (minutes)	16.25	2.50	4.00	1.25	30.00	0.09	YES

Table 3. Mean values and Paired T-test results for the subjective variables for each of the symbiotic activity tools

# Citations

[1] Shastri, D., Fujiki, Y., Buffington, R., Panagiotis, T., and Pavlidis, I., "O' Job Can You Return My Mojo?: Improving Human Engagement and Enjoyment in the Routine Activities", *CHI '10, Proceedings of the 28th international conference on Human factors in computing systems*.

[2] Hill, J.M.D., Ray, C.K., Blair, J.R.S., and Carver, C.A., Jr., "Puzzles and games: addressing different learning styles in teaching operating systems concepts", In *Proceedings of the 34th SIGCSE technical symposium on Computer science education*, pages 182–186, 2003.

[3] Chao, D., "Doom as an interface for process management", In *Proceedings of the SIGCHI conference on Human factors in computing systems*, pages 152–157, 2001

[4] Kuramoto, I., Kashiwagi, K., Shibuya, Y., Tsujino, Y., and Ohtsuka, S., "How can entertainment improve

workers' motivation and their productivity? ", Proceedings of the 2004 ACM SIGCHI International Conference on Advances in computer entertainment technology, p.24-31, June 03-05, 2005, Singapore

[5] Konami Digital Entertainment, http://www.konami.com/games/ddr/

[6] IGN Entertainment, http://ps2.ign.com/articles/669/669004p1.html

[7] Khaled, R., Barr, P., Fischer, R., Noble, J., and Biddle, R. "Factoring culture into the design of a persuasive game", In *Proc. OZCHI* '06, ACM Press (2006), 213- 220

[8] Fisher, C.D., "Effects of external and internal interruptions on boredom at work: Two studies", *Journal of Organizational Behavior* 19, 5 (1998) 503-522